

FIBERFLEX

Fiber Expansion Joint Material for Concrete ASTM 1751



DESCRIPTION

FIBERFLEX Fiber Expansion Joint Filler is composed of cellular fibers securely bonded together and uniformly saturated with asphalt to assure longevity.

FIBERFLEX Fiber Expansion Joint Filler is versatile, resilient, flexible and non extruding.

FIBERFLEX Fiber Expansion Joint Filler will not deform, twist or break with normal on-the-job handling. Breakage, waste and functional failure resulting from the use of inferior, foreign fiber materials can cost you time and dollars.

FIBERFLEX Fiber Expansion Joint Filler fits the bill for virtually any commercial or residential application.

USES

From airport runways to interstate highways, from parking garages to driveways, **FIBERFLEX** prevents damage to concrete caused by expansion. **FIBERFLEX** is proprietary wood fiber blend of treated wood fibers and additives which yields flexible, easy to handle boards. It's stronger and lighter than other expansion joint filler compounds. It's easy to install, resists breakage, cuts cleanly and is easily held in position during pouring.

LEED INFORMATION

MR Credit 4.1: Recycled Content., 10%
 MR Credit 5.1: Locally Produced Materials, 10%
 EQ Credit 4.4: Environmental Quality
 NAHB 606.2(6): Certified Wood

PACKAGING and FEATURES

JDR Joint Packs Feature:

- Proprietary JDR YELLOW shrink-wrap bundles
- Retail and Contractor friendly packaging
- 100 lineal foot bundles
- Product label with UPC codes

FIBERFLEX utilizes a proprietary manufacturing process which imparts:

- Larger compression range
- Greater recovery
- Enhances flexibility

FIBERFLEX JDR Joint Packs provide the perfect protection in the warehouse or on the jobsite.

- Less breakage
- Weather resistant
- Clean, stain free packages
- Easy to handle

FIBERFLEX Expansion Joint Filler Typical Physical Properties	
Compression	265-303 psi
Extrusion	0.016-0.021 inch
Recovery	88%
Density	21 lb/ft ³
Water Absorption	12%
Asphalt Content	35%
Slitability	Excellent
Handleability	Excellent

Packaging Guide on Reverse Side ⇨

FIBERFLEX

Fiber Expansion Joint Material for Concrete ASTM 1751

PACKAGING GUIDE

FIBER EXPANSION JOINT IN YELLOW JOINT-PACK SHRINK SLEEVES

JDR PRODUCT #	PACKAGING INDICATION	CUT SIZE	LFT PER BDLE	PCS PER BDLE	LBS PER BDLE	BDLES PER PLT (CLF)	LFT PER PLT	BDLE SIZE	LBS PER PALLET
JF12C3005	1 07 26842 03531 0	1/2" X 3" X 05'	100	20	25	64	6400	6" X 5" X 60"	1600
JF12C3010	1 07 26842 03031 5	1/2" X 3" X 10'	100	10	25	128	12800	3" X 5" X 120"	3200
JF12C3505	1 07 26842 03571 6	1/2" X 3-1/2" X 5'	100	20	30	56	5600	7" X 5" X 60"	1680
JF12C3510	1 07 26842 03071 1	1/2" X 3-1/2" X 10'	100	10	30	112	11200	3.5" X 5" X 120"	3360
JF12C4005	1 07 26842 03541 9	1/2" X 4" X 5'	100	20	34	48	4800	8" X 5" X 60"	1632
JF12C4010	1 07 26842 03041 4	1/2" X 4" X 10'	100	10	34	96	9600	4" X 5" X 120"	3264
JF12C5005	1 07 26842 03551 8	1/2" X 5" X 5'	100	20	42	40	4000	10" X 5" X 60"	1680
JF12C5010	1 07 26842 03051 3	1/2" X 5" X 10'	100	10	42	80	8000	5" X 5" X 120"	3360
JF12C5505	1 07 26842 03511 2	1/2" X 5-1/2" X 5'	100	20	46	36	3600	11" X 5" X 60"	1656
JF12C5510	1 07 26842 03011 7	1/2" X 5-1/2" X 10'	100	10	46	72	7200	5.5" X 5" X 120"	3312
JF12C6005	1 07 26842 03561 7	1/2" X 6" X 5'	100	20	50	32	3200	12" X 5" X 60"	1600
JF12C6010	1 07 26842 03061 2	1/2" X 6" X 10'	100	10	50	64	6400	6" X 5" X 120"	3200

Packaged and distributed by



THE J D RUSSELL COMPANY

CORPORATE OFFICE
P.O. Box 36795
Tucson, AZ 85740
(520) 742-6194
FAX (520) 293-2202



WESTERN REGION
5488 Reflex Drive
Las Vegas, NV 89156
(800) 888-7425
FAX (520) 293-2202

SOUTHERN REGION
P.O. Box 311
Farmersville, TX 75442
(270) 826-7008
(800) 888-6872
FAX (270) 826-7018

MANUFACTURING FACILITY
P.O. Box 311
Farmersville, TX 75442
(972) 782-8760

NORTHERN REGION
P.O. Box 183471
Shelby Township, MI 48318
(586) 254-8500
(800) 888-9708
FAX (586) 254-8555

SOUTHERN WAREHOUSE & DISTRIBUTION
Jacksonville, FL 32258
(800) 888-6872
FAX (270) 826-7018